

15, 1985 will be authorized by the Commission to continue to operate as long as such operations are found not to cause any unacceptable levels of adjacent satellite interference. In either case, the Commission will impose appropriate terms and conditions in its authorization of such facilities and operations.

(g) The antenna performance standards of small antennas operating in the 12/14 GHz band with diameters as small as 1.2 meters starts at 1.25° instead of 1° as stipulated in paragraph (a) of this section.

[48 FR 40255, Sept. 6, 1983, as amended at 50 FR 2675, Jan. 18, 1985; 50 FR 39004, Sept. 26, 1985; 58 FR 13420, Mar. 11, 1993]

§ 25.210 Technical requirements for space stations in the Fixed-Satellite Service.

(a) All space stations in the Fixed-Satellite Service used for domestic service in the 4/6 GHz frequency band shall:

(1) Use orthogonal linear polarization with one of the planes defined by the equatorial plane;

(2) Be designed so that the polarization sense of uplink transmissions is opposite to that of downlink transmissions on the same transponder; and

(3) Shall be capable of switching polarization sense upon ground command.

(b) All space stations in the Fixed-Satellite Service in the 20/30 GHz band shall use either orthogonal linear or orthogonal circular polarization. Those space stations utilizing orthogonal linear polarization shall also comply with paragraph (a) of this section.

(c) All space stations in the Fixed-Satellite Service shall have a minimum capability to change transponder saturation flux densities by ground command in 4 dB steps over a range of 12 dB.

(d) All space stations in the Fixed-Satellite Service in the 20/30 GHz band shall employ state-of-the-art full frequency reuse either through the use of orthogonal polarizations within the same beam and/or through the use of spatially independent beams.

(e) All space stations in the Fixed-Satellite Service shall be designed to derive the maximum capacity feasible from the assigned orbital location. In

particular, space stations in the Fixed-Satellite Service are required to employ state-of-the-art full frequency reuse using both horizontal and vertical polarization.

(f) For fixed-satellite space stations providing domestic service, full frequency re-use is defined as re-use of the frequency bands by polarization discrimination in both the uplink and downlink directions using state-of-the-art equipment and techniques.

(g) For fixed-satellite space stations providing international service, full frequency re-use is defined as follows:

(1) Satellites must employ polarization discrimination so that, through the use of dual polarization, they shall be able to reuse both the uplink and downlink frequency band assignments.

(2) Satellites must be configured so that all assigned frequencies (in both polarizations) could be reused in beams serving widely separate areas.

(h) [Reserved]

(i) Space station antennas in the Fixed-Satellite Service must be designed to provide a cross-polarization isolation such that the ratio of the on axis co-polar gain to the cross-polar gain of the antenna in the assigned frequency band shall be at least 30 dB within its primary coverage area.

(j) Space stations to be operated in the geostationary satellite orbit must be:

(1) Designed with the capability of being maintained in orbit within 0.05° of their assigned orbital longitude,

(2) Maintained in orbit at their assigned orbital longitude within the longitudinal tolerance specified by the Commission, and

(3) The Commission may authorize operations at assigned orbital longitudes offset by 0.05° or multiples thereof from the nominal orbital location specified in the station authorizations.

(k) Antenna measurements of both co-polarized and cross-polarized performance must be made on all antennas employed by space stations both within the primary coverage area to facilitate coordination with other Commission space station licensees and outside the primary coverage area to facilitate international frequency coordination with other Administrations.

The results of such measurements shall be submitted to the Commission within thirty days after preliminary in-orbit testing is completed.

(l) All operators of space stations shall, on June 30 of each year, file a report with the International Bureau and the Commission's Columbia Operations Center in Columbia, Maryland, containing the following information current as of May 31 of that year:

(1) Status of satellite construction and anticipated launch dates, including any major problems or delays encountered;

(2) A listing of any non-scheduled transponder outages for more than thirty minutes and the cause(s) of such outages;

(3) A detailed description of the utilization made of each transponder on each of the in-orbit satellites. This description should identify the total capacity or the percentage of time each transponder is actually used for transmission, and the amount of unused system capacity in the transponder. This information is not required for those transponders that are sold on a non-common carrier basis. In that case, operators should indicate the number of transponders sold on each in-satellite orbit.

(4) Identification of any transponders not available for service or otherwise not performing to specifications, the cause of these difficulties, and the date any transponder was taken out of service or the malfunction identified.

[58 FR 13420, Mar. 11, 1993, as amended at 61 FR 9952, Mar. 12, 1996; 62 FR 5931, Feb. 10, 1997; 62 FR 61457, Nov. 18, 1997]

§ 25.211 Video transmissions in the Fixed-Satellite Service.

(a) Downlink analog video transmissions in the band 3700–4200 MHz shall be transmitted only on a center frequency of $3700+20N$ MHz, where $N=1$ to 24. The corresponding uplink frequency shall be 2225 MHz higher.

(b) All 4/6 GHz analog video transmissions shall contain an energy dispersal signal at all times with a minimum peak-to-peak bandwidth set at whatever value is necessary to meet the power flux density limits specified in § 25.208(a) and successfully coordi-

nated internationally and accepted by adjacent U.S. satellite operators based on the use of state of the art space and earth station facilities. Further, all transmissions operating in frequency bands described in § 25.208 (b) and (c) shall also contain an energy dispersal signal at all times with a minimum peak-to-peak bandwidth set at whatever value is necessary to meet the power flux density limits specified in § 25.208(b) and (c) and successfully coordinated internationally and accepted by adjacent U.S. satellite operators based on the use of state of the art space and earth station facilities. The transmission of an unmodulated carrier at a power level sufficient to saturate a transponder is prohibited, except by the space station licensee to determine transponder performance characteristics. All 12/14 GHz video transmissions for TV/FM shall identify the particular carrier frequencies for necessary coordination with adjacent U.S. satellite systems and affected satellite systems of other administrations.

(c) All initial analog video transmissions shall be preceded by a video test transmission at an uplink e.i.r.p. at least 10 dB below the normal operating level. The earth station operator shall not increase power until receiving notification from the satellite network control center that the frequency and polarization alignment are satisfactory pursuant to the procedures specified in § 25.272. The stationary earth station operator that has successfully transmitted an initial video test signal to a satellite pursuant to this paragraph is not required to make subsequent video test transmissions if subsequent transmissions are conducted using exactly the same parameters as the initial transmission.

(d) In the 6 GHz band, an earth station with an equivalent diameter of 9 meters or smaller may be routinely licensed for transmission to full transponder services if the maximum power into the antenna does not exceed 450 watts (26.5 dBW). In the 14 GHz band, an earth station with an equivalent diameter of 5 meters or smaller may be routinely licensed for transmission of